



Rugged, Bluetooth sub-meter Mapping receiver

The SXBlue II GPS is a compact, real-time receiver that delivers true sub-meter performance every second to your application. Its integrated lightweight design makes it the ideal choice for a variety of industry applications including GIS, Forestry, Mining, Utilities, Agriculture, Survey and Environmental, at a price you can afford.

Go Real-time, All the Time!

The SXBlue II GPS uses innovative technology that delivers sub-meter accuracy in real-time, all the time. There is no need for post-processing or a beacon receiver when WAAS, EGNOS, MSAS, or GAGAN are available. Even in forestry applications and other difficult mapping environments where GPS reception is limited, the SXBlue II is designed to keep working and deliver the DGPS accuracy you need all day long.

Accuracy and Productivity in One

The SXBlue II GPS takes real-time accuracy a step further. Its accurate code phase measurements and leading edge multipath mitigation delivers sub-60 cm (2dRMS, 95% confidence) positioning.

With its superior tracking performance and innovative real-time positioning, that means no downtime even in harshest conditions, the SXBlue II maximizes your productivity by working directly within your GIS framework (ESRI, Autodesk, CMT, Integraph, MapInfo, TDS, etc.) both in the field and the office.

A Long Term Solution

Add a field computer that suits your application, an off-the-shelf software of your choice, and the SXBlue II GPS becomes the heart of a modular

solution you can grow with. In today's rapidly evolving technologies, its unique multi-port interface (fully independent Bluetooth, USB, RS-232 ports) helps to protect your long term investment by always allowing the use of up-to-date computer hardware, operating system and software.

Options

The SXBlue II GPS can also evolve with your needs with its optional features:

- 10Hz or 20Hz output rates
- Base Station (standard RTCM-104 output)
- Proprietary RTCM for sub-30cm accuracy
- Single Frequency Real-time Kinematic (RTK) for cm level accuracy
- Carrier Phase for post-processed cm level accuracy

Key Features

- Sub-60cm, 2dRMS real-time performance
- Multi-port interface (Bluetooth, USB, RS-232)
- Rugged and Waterproof design
- Integrated Li-Ion battery pack for 10+ hours autonomy
- Battery fuel gauge
- Compact and lightweight
- RoHS compliant

Specifications

GPS Sensor

Receiver Type:	L1, C/A code, with carrier phase smoothing
Channels:	12-channel, parallel tracking (10-channel when tracking SBAS)
SBAS Support:	2-channel, parallel tracking WAAS, EGNOS, MSAS, GAGAN, and compatible. SBAS Ranging
Update Rate:	2Hz default, optional 10 and 20Hz
DGPS Horizontal Accuracy: (with SBAS)	< 60cm 2dRMS, 95% confidence ¹ (< 30cm HRMS, < 25cm CEP)
Horizontal Accuracy: (Autonomous)	< 2.5m 2dRMS, 95% confidence (autonomous, no SA) ²
Optional Proprietary RTCM:	< 30cm 2dRMS, 95% confidence ³
Optional L1 RTK:	< 2cm 2dRMS, 95% confidence ³
Cold Start:	60s (no almanac or RTC)
Reacquisition:	< 1s
Maximum Speed:	1607 km/h (999mph)
Maximum Altitude:	18,288m (60,000 ft)

Communication

Ports:	Bluetooth, RS-232C, USB 2.0
Bluetooth Transmission:	Class 1, 250m typical range ⁴
Bluetooth Frequency:	2.400 – 2.485 GHz
Fully Bluetooth pre-qualified:	Bluetooth 2.0
Baud Rates:	4800 to 57600
Data I/O Protocol:	NMEA 183, Binary
Data Output Datum:	Autonomous: WGS 84 (G1150) SBAS: ITRF-2000
Timing Output:	1 PPS (HCMOS, active high, rising edge sync, 10 kOhms, 10 pF load)
Event Marker Input:	HCMOS, active low, falling edge sync, 10 kOhms, 10 pF load
Raw Measurement Data:	Proprietary binary (Free RINEX utility)
Correction I/O Protocol:	RTCM SC-104, Optional Proprietary format
GPS Status LED:	Power, GPS lock, DGPS position, DIFF lock, Bluetooth connection
Battery Status LED:	5 LED's bar graph

Power

Battery type:	Field replaceable Lithium-Ion pack (Rechargeable in unit)
Battery Capacity:	3,900mAh. 7.2V (Average autonomy: 10+ hours)
Power Consumption:	< 2.5W
Charging Time:	4-5 hours (with supplied charger)
Antenna Voltage Output:	5 VDC
Antenna Input Impedance:	50 Ohms

Environmental

Operating Temperature:	-40°C to +85°C (-40°F to +185°F) ⁵
Storage Temperature:	-40°C to +85°C (-40°F to +185°F)
Humidity:	95% non-condensing
Compliance:	FCC, CE, RoHS and Lead-free

Mechanical

Enclosure Material:	Re-enforced Nylon
Battery Case Material:	ABS
Enclosure Rating:	Waterproof, IP-67
Immersion:	30cm, 30 minutes
Enclosure Dimensions:	14.1 x 8.0 x 4.7 cm (5.57 x 3.15 x 1.85 in.)
Weight:	464g (1.02 lbs)
Data Connectors:	DB-9 Female USB Type B Female
Antenna Connector:	SMA Female

Antenna

GPS Frequency Range:	L1 (1575 MHz +/- 10 MHz)
Gain (without cable):	26.5 dB (+/- 2 dB), 35mA
Voltage:	+5 VDC +/- 10%
Impedance:	50 Ohms
Dimensions:	5.5 diam. x 2.2 cm (2.16 x .87 in.)
Weight (without cable):	79g (.17 lbs) (with removable magnet mount)
Antenna Connector:	SMA Female
Finish:	Fluid Resistant
Temperature:	-55°C to +85°C (-67°F to +185 °F)
Humidity:	Immersion 1 meter

Standard Accessories

SXBlue II GPS Receiver
Li-Ion Battery Pack (Field replaceable)
Li-Ion Charger
Belt/Shoulder Carrying Case
Precision Antenna with 1.5m cable
Soft Hat for antenna
RS-232 Cable (6 ft)
USB Type A/B Cable (6 ft)
CD-ROM (manuals and utilities)

Field Activated Options

10Hz or 20Hz Output Rate
Base Station RTCM Output
Proprietary Real-time for <30cm
L1 RTK for <2cm

NOTES :

1. Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for local services) and ionospheric activities
2. Depends on multipath environment, number of satellites in view, satellite geometry and ionospheric activities
3. Option required on both base and rover. Also requires communication link between base and rover. Stated accuracies for baseline lengths of 5 km
4. Transmission in free space
5. Lithium-Ion battery performance degrades below -20°C (-4°F)

© Copyright March 2007, Geneq inc. All rights reserved. Specifications subject to change without notice. The Bluetooth™ trademarks are owned by Bluetooth SIG, Inc, U.S.A. Made in Canada.

